

Since 1982

TRADCO

Defining the Details

Door Lever Fitting Instructions

Contents

2 x Door levers (one set)	4 x Tie bolts
2 x Rose covers	2 x Sprung spindles (two halves)
8 x Wood screws	1 x Regular spindle

These levers can be face-fixed with the wood screws provided, or fixed through the door using the tie bolts. The tie bolts provide a stronger fixing method and we recommend their use where the lock or latch fitted (supplied separately) has a bolt-through hole.

Two styles of spindle are provided; sprung halves and a regular spindle. Both perform the same function, however we recommend using the sprung halves where possible as they avoid the need to cut the spindle to size and provide for smooth operation.

The following instructions are provided for use with tie bolts, however can be easily applied to a face-fixing application.

Tie Bolt Fix

1. Unscrew the rose covers to expose the inner fitting plates.
2. Place spindle halves in the levers and insert into the follower of the previously installed lock or latch in order to mark the fitting plate screw holes.
3. Once holes are marked, set the levers to the side and drill the fixing holes.
4. Place the lever with the non-threaded tie bolt holes (refer image below) back onto lock/latch and insert the tie bolts through the non-threaded holes and through the door.
5. Take the threaded half of the lever set and place the spindle in the follower while lining up the tie bolts with the threaded holes.
6. Tighten the tie bolts. If the tie bolts are too long they will need to be shortened at one of the three shortening points using cutting pliers.
7. Check that all fixings are tightened before testing the operation of the lever.
8. Once it is working correctly, replace the rose covers and tighten by hand.

Further fitting instructions, templates, care & maintenance information and instructional videos can be found at our websites: tradco.com.au tradco.co.nz

